

# Technical Information

---

## Adhesin 114

<b>TYPE</b>	: Emulsion
<b>PHYSICAL PROPERTIES</b>	: Appearance : White Viscosity : 6500-8000 cps ( BF RVF 4/10/27 <sup>0</sup> C ) Solids : 55 - 58 % S.G. : 1.03 - 1.07 pH : 4.0 - 5.0 Flammability : Not flammable
<b>OPERATING CONDITIONS</b>	: Ready for use as supplied. Dilute with water if required. Direct transfer from brush, roller or glue spreader
<b>SUGGESTED USES</b>	: Case Sealing ( varnish surface) It confirms to composition requirement of FDA regulations 21CFR 175.105 “ Adhesives”
<b>PRECAUTIONS</b>	: Store in closed containers to prevent drying out and contamination. Rotate stock - first in - first out. Do not mix with other adhesives. Recommended to use the adhesive within 6 months.
<b>PACKAGE</b>	: 50 Kg HDPE Drum / 200 kg MS drum

### **Henkel CAC Pvt. Ltd.**

*Plot No. 1/1 Part 2, TTC Indl. Area, Thane Belapur Road,  
Koparkhairne, Navi Mumbai- 400710  
Tel: +91-22- 27787371 Fax: +91-22-27780025*

