## **Technical Information**

## **Technomelt Q 299M**

**TYPE** : Hot Melt

PHYSICAL PROPERTIES : Appearance : Pigment White

> : 4480 - 6720 cps @180°C Viscosity

> > 5680 - 8520 cps @170°C 7520 - 11280 cps @160°C

Softening Point: 92 +/- 4°C Form : Chip or Granules

Storage Life : 12 months

**OPERATING CONDITIONS** : Can be used in all standard roller, wheel and nozzle applicators.

> : 160 - 180°C Running Temperature Setting Speed : Medium Open time : Medium

**SUGGESTED USES** : Perfect Bookbinding

> It also conforms to composition requirements of FDA regulation 21 CFR 175.105 "Adhesives".

**PRECAUTIONS** : Material is applied hot. Appropriate clothing and gloves should

be used.

Keep containers and premelters covered to avoid contamination.

Rotate stock -first in- first out

**PACKAGE** : 25 Kg/HDPE Bag

## Henkel CAC Pvt. Ltd.

Plot No. 1/1 Part 2, TTC Indl. Area, Thane Belapur Road, Koparkhairne, Navi Mumbai- 400710 Tel: +91-22-27787371 Fax: +91-22-27780025

**Technologies** Industrial Adhesives

TDS-Technomelt Q 299M Page 1 Status: August 2010