Technical Information

Technomelt Q 718 WHITE

| ТҮРЕ | : Hot Melt |
|----------------------|---|
| PHYSICAL PROPERTIES | : Appearance : Pigment White Viscosity : 6000 - 10000 cps @170°C Softening Point : 89 +/- 4°C Form : Chip or granules Storage Life : 12 months |
| OPERATING CONDITIONS | Can be used in all standard roller, wheel and nozzle applicators. Running Temperature : 160 - 180°C Setting Speed : Medium Open time : Medium |
| SUGGESTED USES | : Perfect Bookbinding It also conforms to composition requirements of FDA regulation 21 CFR 175.105 "Adhesives". |
| PRECAUTIONS | Material is applied hot.Appropriate clothing and gloves should be used. Keep containers and premelters covered to avoid contamination. Rotate stock -first in- first out. |
| PACKAGE | : 25 Kg/HDPE Bag |

Henkel CAC Pvt. Ltd.

Plot No. 1/1 Part 2, TTC Indl. Area, Thane Belapur Road, Koparkhairne, Navi Mumbai- 400710 Tel: +91-22- 27787371 Fax: +91-22-27780025



TDS-Technomelt Q 718 WHITE Page 1

Status: August 2010

Data is given as a guide to a products suggested use. Prospective users are strongly advised to undertake adequate tests under their own conditions on substrates to be used and with reference to the conditions of use of the final product before the above adhesive is adopted commercially. Any changes in these performance parameters should be preceded by similar tests