## **Technical Information**

## Technomelt Q 970

**TYPE** : Hot Melt

**PHYSICAL PROPERTIES** : Appearance : Pigment white

Viscosity : ~ 2500 cps @180°C

2750 - 4500 cps @170°C

~ 4750 cps @160° C

Softening point : 74 +/- 4°C

Form : Chips or granules

Storage Life : 12 months at ambient temperature

**OPERATING CONDITIONS** : Can be used in all standard roller, wheel and nozzle applicators.

Running Temperature : 160 - 180°C Setting Speed : Medium Open time : Medium

**SUGGESTED USES**: Perfect Bookbinding.

It also conforms to composition requirements of FDA regulation 21 CFR 175.105 "Adhesives".

**PRECAUTIONS** : Material is applied hot. Appropriate clothing and gloves should

be used.

Keep containers and premelters covered to avoid contamination.

Rotate stock -first in- first out

PACKAGE : 25 Kg/HDPE Bag

## Henkel CAC Pvt. Ltd.

Plot No. 1/1 Part 2, TTC Indl. Area, Thane Belapur Road, Koparkhairne, Navi Mumbai- 400710

Tel: +91-22-27787371 Fax: +91-22-27780025

Henkel
Technologies
Industrial Adhesives

TDS-Technomelt Q 970 Page 1 Status: August 2010

Data is given as a guide to a products suggested use. Prospective users are strongly advised to undertake adequate tests under their own conditions on substrates to be used and with reference to the conditions of use of the final product before the above adhesive is adopted commercially. Any changes in these performance parameters should be preceded by similar tests