



PRODUCT DATA SHEET

Adhesin 053A LV

- TYPE** : Emulsion
- PHYSICAL PROPERTIES** : Appearance : White, fluid
Viscosity : 700-1000 cps
(BF RVT 3/10/27⁰C)
Solids : 54 - 56 %
pH : 4-5
Flammability : Not flammable
- OPERATING CONDITIONS** : Ready for use as supplied. Dilute with water when required. Direct transfer from, wheel or glue spreader
- SUGGESTED USES** : Adhesin 053ALV is specially formulated for glue lap operation requiring very fast drying speed.
- It conforms to composition requirements of FDA regulation 21 CFR 175.105 “ Adhesives “.
- PRECAUTIONS** : Store in closed containers to prevent drying out and contamination.
Rotate stock - first in - first out.
Do not mix with other adhesives.
Recommended to use the adhesive within 12 months.
- PACKAGE** : 50 Kg HDPE Drum / 200 kg MS drum

*Plot No. 1/1, TTC Indl. Area
Thane Belapur Road
Koparkhairne, Navi Mumbai- 400709*

INDIA

Data is given as a guide to a products suggested use. Prospective users are strongly advised to undertake adequate tests under their own conditions on substrates to be used and with reference to the conditions of use of the final product before the above adhesive is adopted commercially. Any changes in these performance parameters should be preceded by similar tests